


## 57kW DIESEL HYDRAULIC POWER UNIT - ATEX ZONE 2



## 57kW DIESEL HYDRAULIC POWER UNIT - ATEX ZONE 2

Brimmond's compact 57kW Diesel Driven HPU can be used either onshore or offshore to provide a hydraulic power solution for:

- Hydraulic spoolers/reelers
- Marine cranes
- Diver tooling
- Winches
- Casing tongs
- Hydraulic flushing

Brimmond offer a range of complimentary equipment for rental; contact our hire team to find out how we can help you. For special projects, we offer a bespoke design solution, tailored to your requirements.

ToftHills Avenue, Midmill Business Park,  
Kintore, Aberdeenshire, Scotland, AB51 0QP, UK

+44 (0) 1467 633805  
info@brimmond.com



www.brimmond.com

# BRIMMOND

## WORK AREA CLASSIFICATION




 Group II Category 3 (Zone 2) Gas Group IIB  
 Temperature Class T4

## TECHNICAL SPECIFICATION - STANDARD SUPPLY

ENGINE TYPE	JCB 444NA
STARTER	Jetstream ATEX air turbine starter
ENGINE OUTPUT	57kW @ 2200rpm (continuous) • 63kW @ 2200rpm (Intermittent)
PUMP TYPE	Main: 112cc Kawasaki variable displacement piston pump Auxiliary: Hydra-permco fixed displacement gear pump
PUMP OUTPUT (MAX FLOW)	224lpm @ 138 Bar*
PUMP OUTPUT (MAX PRESSURE)	320 Bar @ 97lpm* Auxiliary Pump: 25l/min, 210 Bar
FILTRATION	90-micron suction, 3-micron pressure and 20-micron return (as standard, others available on request)
OIL TANK CAPACITY	460 litres
OIL TYPE	ISO 32 as standard, others on request
HYDRAULIC CONNECTIONS	Quick release couplings (client specified type) Main Pump: Pressure: 1" NPT Female • Return: 1 1/4" NPT Female • Case Drain: 3/4" NPT Female Auxiliary Pump: Pressure: 3/4" NPT Female • Return: 1 1/4" NPT Female • Case Drain: 1/2" NPT Female
FUEL TANK CAPACITY	225 litres
CONTROL PANEL	<ul style="list-style-type: none"> <li>• Side mounted • Main pump load/unload • Auxiliary pump load/unload • Engine rpm • Main pump pressure</li> <li>• Auxiliary pump pressure • Exhaust temperature</li> <li>• Coolant temperature • Hydraulic oil temperature</li> </ul>
SAFETY FEATURES	<ul style="list-style-type: none"> <li>• Fully enclosed unit • ESD switch • Low oil shutdown</li> <li>• High temperature overspeed shut down</li> <li>• Pressure relief valve</li> </ul>
MOVING & HANDLING	DNV 2.7-3, Type A, Class R60 • 4-leg certified sling set • Forklift pockets
DIMENSIONS	2500mm (L) x 1500mm (W) 2090mm (H)
WEIGHT	3,000kgs (gross)

## MAIN DIMENSIONS



All information is correct at the time of printing. Brimmond reserves the right to make any changes to the above specification, without prior notice, with no impact on the overall unit performance.

BGF-109-REV 02

\*other flow and pressures available on request

 BRIMMOND