




15,000PSI HYDROSTATIC PRESSURE TEST UNIT - ATEX ZONE 1



15,000PSI HYDROSTATIC PRESSURE TEST UNIT - ATEX ZONE 1

Brimmond's 15,000psi Hydrostatic Pressure Test Unit can be used either onshore or offshore to pressure test a variety of different equipment such as:

- Well control equipment
- Manifolds
- High pressure hose assemblies
- Valves
- Motion compensation equipment

Brimmond offer a range of complimentary equipment for rental; contact our hire team to find out how we can help you. For special projects, we offer a bespoke design solution, tailored to your requirements.

Tofthills Avenue, Midmill Business Park,
Kintore, Aberdeenshire, Scotland, AB51 0QP, UK

+44 (0) 1467 633805
info@brimmond.com



www.brimmond.com



WORK AREA CLASSIFICATION




Group II Category 2 (Zone 1) Gas Group IIB
Temperature Class T3

TECHNICAL SPECIFICATION - STANDARD SUPPLY

PUMP TYPE	HII air driven piston pumps
AIR SUPPLY REQUIREMENTS	75 SCFM @ 100psi (maximum)
HIGH PRESSURE PUMP OUTPUT	1lpm @ 16,500psi
LOW PRESSURE PUMP OUTPUT	25lpm @ 800psi
HIGH PRESSURE CHART RECORDER RANGE	0-20,000psi
LOW PRESSURE CHART RECORDER RANGE	0-1,000 psi
HIGH PRESSURE PRV SETTING	Adjustable up to 16,500psi
LOW PRESSURE PRV SETTING	Adjustable up to 900psi
CONTROL PANEL	<ul style="list-style-type: none"> • Schematic overview for ease of operation • Emergency stop button • System pressure dump valve • Low fluid level indicator • Air supply isolation & regulators • Pressure selector valve • Low air supply pressure indicator
INSTRUMENTATION	<ul style="list-style-type: none"> • Panel mounted dual scale chart recorder • Air supply and system pressure gauges
PROCESS CONNECTIONS	9/16" medium pressure male on 20m hose
PROCESS MEDIA	Methanol, glycol, water
MOVING & HANDLING	<ul style="list-style-type: none"> • DNV 2.7-3, Type A, Class R60 certified frame • 4-leg certified sling set • Forklift pockets
DIMENSIONS	1500mm (L) x 1310mm (W) x 2000mm (H)
WEIGHT	3,000kg (gross)

MAIN DIMENSIONS



All information is correct at the time of printing. Brimmond reserves the right to make any changes to the above specification, without prior notice, with no impact on the overall unit performance.