

## 2" FLUID MANIFOLDS



## 2" FLUID MANIFOLDS

Brimmond's range of lightweight, stainless steel fluid manifolds can be used either onshore or offshore for applications such as:

- Hot oil flushing
- Chemical cleaning
- Pipeline flooding
- Well testing
- Tank cleaning
- Fluid transfer

Brimmond offer a range of complimentary equipment for rental; contact our hire team to find out how we can help you. For special projects, we offer a bespoke design solution, tailored to your requirements.

Tofthills Avenue, Midmill Business Park,  
Kintore, Aberdeenshire, Scotland, AB51 0QP, UK

+44 (0) 1467 633805  
info@brimmond.com



www.brimmond.com

## TECHNICAL SPECIFICATION - STANDARD SUPPLY

NUMBER & TYPE OF VALVES	10 x 2" quarter turn full port 316 stainless steel ball valve
PROCESS CONNECTIONS	Options: 10 x 2" Camlock 10 x 2" BSPP Male
PROCESS MEDIA	Water, oil, fluid
PIPE SIZE	3" SCH 40 stainless steel
MAXIMUM WORKING PRESSURE	150psi
MOVING & HANDLING	Handles, foot plates
DIMENSIONS	830mm (L) x 625mm (W) x 237mm (H)
WEIGHT	65kg

## MAIN DIMENSIONS

