



PNEUMATIC HYDRAULIC POWER UNIT



PNEUMATIC HYDRAULIC POWER UNIT

Brimmond's Pneumatic Hydraulic Power Unit can be used either onshore or offshore to provide hydraulic power to a variety of equipment such as:

- Hydraulic cylinder actuation
- Confined space hydraulic power

Brimmond offer a range of complimentary equipment for rental; contact our hire team to find out how we can help you. For special projects, we offer a bespoke design solution, tailored to your requirements.

ToftHills Avenue, Midmill Business Park,
Kintore, Aberdeenshire, Scotland, AB51 0QP, UK

+44 (0) 1467 633805
info@brimmond.com



www.brimmond.com





WORK AREA CLASSIFICATION

CE Safe Area use only

TECHNICAL SPECIFICATION - STANDARD SUPPLY

AIR REQUIREMENTS	220cfm @ 100psi
PUMP OUTPUT	11lpm @ 3200psi
FILTRATION	25N micron return filter
OIL TANK CAPACITY	55 litres
OIL TYPE	32wt hydraulic oil
HYDRAULIC CONNECTION	1/2" flat face quick release coupling
CONTROL	Air regulator, air supply shut off valve, DCV on request
MOVING & HANDLING	Protective crash frame with fold out manual handles
DIMENSIONS	500mm (L) x 610mm (W) x 750mm (H)

MAIN DIMENSIONS

All information is correct at the time of printing. Brimmond reserves the right to make any changes to the above specification, without prior notice, with no impact on the overall unit performance.