

4TE O-BOARDING SHEAVE



4TE O-BOARDING SHEAVE

Brimmond's 4Te Overboard Umbilical Sheaves can be used either onshore or offshore to provide a deployment solution for:

- **Hose deployment**
- **Cable deployment**

Brimmond offer a range of complimentary equipment for rental; contact our hire team to find out how we can help you. For special projects, we offer a bespoke design solution, tailored to your requirements.

Tofthills Avenue, Midmill Business Park,
Kintore, Aberdeenshire, Scotland, AB51 0QP, UK

+44 (0) 1467 633805
info@brimmond.com



www.brimmond.com

WORK AREA CLASSIFICATION

CE Safe Area classification

TECHNICAL SPECIFICATION - STANDARD SUPPLY

DESCRIPTION	4Te O-Boarding Sheave
DESIGN STANDARD	Designed and tested in accordance with DNVGL-ST-0378
MAXIMUM SW-LINE PULL	4000kg
SAFETY FEATURES	Upper swing rollers Swivel type top rollers with safety retaining pins Secondary sling retaining point SWL 4.75Te Top mounted swivel hoist ring
UMBILICAL SIZE	Up to 158mm diameter
MINIMUM BEND RADIUS (MBR)	800mm
OPERATING ANGLES	0° Vertical (180° total) 55° to Vertical (110° total)
GROSS WEIGHT	450kg
MOVING & HANDLING	Top swivel hoist ring, SWL 8.5Te and can accept a 8.5Te shackle (shackle supplied on request)
DIMENSIONS	2720mm (L) x 370mm (W) x 1557mm (H)

MAIN DIMENSIONS

