

37KW DIESEL HYDRAULIC POWER UNIT - SAFE AREA



37kW DIESEL HYDRAULIC POWER UNIT - SAFE AREA

Brimmond's compact 37kW Diesel Driven HPU can be used either onshore or offshore to provide a a hydraulic power solution for:

- Hydraulic spoolers/reelers
- Diver tooling
- Casing tongs

- Marine cranes
- Winches
- Hydraulic flushing

Brimmond offer a range of complimentary equipment for rental; contact our hire team to find out how we can help you. For special projects, we offer a bespoke design solution, tailored to your requirements.

Tofthills Avenue, Midmill Business Park, Kintore, Aberdeenshire, Scotland, AB51 OQP, UK

+44 (0) 1467 633805 info@brimmond.com







WORK AREA CLASSIFICATION



TECHNICAL SPECIFICATION - STANDARD SUPPLY

ENGINE TYPE 37-56kW Deutz D2.9 L4 Diesel

STARTER Battery Key start 12Vdc

ENGINE OUTPUT 45kW & 2500rpm

PUMP TYPE Main: Kawasaki Variable Displacement Piston Pump

PUMP OUTPUT (MAXIMUM) Main Pump: 112.51/min, 320 bar

FILTRATION 90-micron scution, 3-micron pressure and 20-micron return

(as standard, others available on request)

OIL TANK CAPACITY XXX litres

OIL TYPE ISO 32 as standard, others on request

HYDRAULIC CONNECTIONS Quick release couplings (client specified type)

Main Pump: Pressure: 3/4" NPT Female • Return 1" NPT Female

Case Drain: 1/2" NPT Female

FUEL TANK CAPACITY 50 litres

CONTROL PANEL

• Side mounted • Main pump load/unload • Engine rpm

• Main pump pressure

SAFETY FEATURES • Fully enclosed unit • ESD switch • Low oil shutdown

• high temperature shutdown • Overspeed shutdown

Pressure relief valve

MOVING & HANDLING • 4-leg certified sling set

Forklift pockets

DIMENSIONS 1900mm (L) x 1050mm (W) x 1310mm (H)

W∈IGHT Gross 1,000kg

MAIN DIMENSIONS







