

OVERBOARD UMBILICAL CHUTE



OVERBOARD UMBILICAL CHUTE

Brimmond's Overboard Umbilical Chutes can be used either onshore or offshore to provide a deployment solution for:

- **Hose deployment**
- **Cable deployment**

Brimmond offer a range of complimentary equipment for rental; contact our hire team to find out how we can help you. For special projects, we offer a bespoke design solution, tailored to your requirements.

Tofthills Avenue, Midmill Business Park,
Kintore, Aberdeenshire, Scotland, AB51 0QP, UK

+44 (0) 1467 633805
info@brimmond.com



www.brimmond.com

WORK AREA CLASSIFICATION

CE Safe Area classification

TECHNICAL SPECIFICATION - STANDARD SUPPLY

DESCRIPTION	Overboard chute
DESIGN STANDARD	Design factor 2:1
MAXIMUM SW-LINE PULL	4550kg @ 90° Angle
SAFETY FEATURES	Removable top nylon rollers, preventing umbilical jumping off during operation
UMBILICAL SIZE	Ø270mm (Maximum)
MINIMUM BEND RADIUS (MBR)	808mm
OPERATING ANGLES	90°
GROSS WEIGHT	230kg
MOVING & HANDLING	Overhead lift (6 x padeyes suitable for 3.5Te shackle)
DIMENSIONS	1950mm (L) x 525mm (W) x 1178mm (H) All dimensions are maximum

MAIN DIMENSIONS

